

SAVEO-M71CR

The pocketable and powerful Mobile Computer for any data capture application



YOUR DAILY COMPANION FOR ALL DATA CAPTURE **ACTIVITIES**

SAVEO-M71CR mobile computer is the perfect pocketable business companion for any data capture application, from assisted sales to the shop floor, or back-end receiving to the warehouse. It might be small in size, but it's very large in technology!

The SAVEO-M71CR mobile computer includes a powerful 2 GHz octacore processor with 3 GB of memory featuring Android™ 9. The backlit keyboard ensures very fast data input, while the 4 inch display provides the user with plenty of space for their applications.

COMMUNICATION AND DESIGN

The powerful Wi-Fi connection which includes AC standard allows users to access very fast download and upload connections, while the USB-C ensures exceptional data exchange and charging speeds.

The SAVEO-M71CR mobile computers' light weight and thin design, along with 2 comfortably positioned side keys and SoftSpot™ technology for a variety of user-defined functions, make scanning processes both easy and fast. It is also very durable with an IP54 rating and 1.2 m / 4 feet drop spec. The 3,800 mAh battery ensures a very long operational scanning session.

KEYBOARD AND SCAN ENGINE

The soft-touch, backlit keyboard allows users to quickly type in information such as quantity, description or location of any item scanned. The lightning fast 2D imager allows users to easily read any 1D or 2D barcode from any surface, including mobile screens.

FEATURES

- Ultra-Ergonomic, compact and robust
- 4 inch capacitive multi-touch display with Dragontrail™ hardened glass
- Android 9
- 2 GHz, Quad/Octa CPU with 3 GB RAM / 32 GB Flash
- Backlit 24 key rubber keyboard, plus two side scan keys and two programmable side
- Replaceable 3,800 mAh Li-Ion Battery
- Ruggedized with drop resistance to 1.2 m / 4 ft to concrete (1.5 m / 5 ft with rubber boot) and IP54 sealing
- Powerful Wi-Fi including the latest 802.11ac standard
- Bluetooth® v5 short range wireless technology and BLE
- NFC for proximity communications
- Rear camera with auto focus, 8 MP with flash LED
- Advanced 2D ultra-slim VGA imager with Datalogic's patented 'Green Spot' technology for visual good-read feedback
- Datalogic's SoftSpot™ technology for innovative triggering through the touch display
- EASEOFCARE Service Plans offer a wide range of options to protect your investment, ensuring maximum productivity and ROI.













INDUSTRY - APPLICATION

- · Shop floor applications
- Online order fulfilment

- ReceivingManual picking (PTG)Order verification

- Production and quality control
- Inventory management

- Pharmacy In-store operationsPharmacy/Hospital pharmacy Inventory management
- Pharmacy warehouse/Hospital pharmacy warehouse -
- Home healthcare

NOTE: The Android robot is reproduced or modified from work

SAVEO-M71CR

TECHNICAL SPECIFICATIONS

WIRELESS COMMUNICATIONS	
Local Area Network (WLAN)	IEEE 802.11 a/b/g/n/ac/d/e/i/w; Frequency range: Country dependent, typically 2.4 GHz and 5 GHz bands
Personal Area Network (WPAN)	Bluetooth wireless technology v5 (Classic Bluetooth wireless technology and BLE)
NFC Communication	Support for the following standards: ISO14443-4 (type-A, type-B); ISO15693; Mifare; Felica
DECODING CAPABILITY	
1D / Linear Codes	Auto discriminates all standard 1D codes including GS1 DataBar™ linear codes.
2D Codes	Aztec Code, Data Matrix, HanXin Code, MaxiCode, MicroQR Code, QR Code, EAN/JAN Composites, UPC A/E Composites
Postal Codes	Australian Post, Japan Post, British Post; China Post; IMB, Korea Post, KIX Code, PLANET, POSTNET, Royal Mail Code (RM4SCC)
Stacked Codes	Micro-PDF417, MacroPDF, PDF417, GS1 DataBar Composites, GS1 DataBar Expanded Stacked, GS1 DataBar Stacked, GS1 DataBar Stacked Omnidirectional
ELECTRICAL	
Battery	Removable battery pack 3800 mAh with rechargeable Li-Ion batteries
ENVIRONMENTAL	
Drop Resistance	Withstands drops from 1.2 m / 4 ft to concrete according to IEC62-2-32 Method 1. Device with rubber boot: withstands drops from 1.5 m / 5 ft to concrete according to IEC62-2-32 Method 1 with rubber boot.
	Device: exceeds 400 hits at 0.5 m (200 cycle) per IEC
Tumbles	60068-2-32 specification. Device with rubber boot: exceeds 600 hits at 0.5 m (300 cycle) per IEC 60068-2-32 specification.
Tumbles Particulate and Water Sealing	60068-2-32 specification. Device with rubber boot: exceeds 600 hits at 0.5 m (300
Particulate and Water	60068-2-32 specification. Device with rubber boot: exceeds 600 hits at 0.5 m (300 cycle) per IEC 60068-2-32 specification.
Particulate and Water Sealing	60068-2-32 specification. Device with rubber boot: exceeds 600 hits at 0.5 m (300 cycle) per IEC 60068-2-32 specification. IP54 Operating: -20 to 50 °C / -4 to 122 °F
Particulate and Water Sealing Temperature	60068-2-32 specification. Device with rubber boot: exceeds 600 hits at 0.5 m (300 cycle) per IEC 60068-2-32 specification. IP54 Operating: -20 to 50 °C / -4 to 122 °F
Particulate and Water Sealing Temperature	60068-2-32 specification. Device with rubber boot: exceeds 600 hits at 0.5 m (300 cycle) per IEC 60068-2-32 specification. IP54 Operating: -20 to 50 °C / -4 to 122 °F Storage/Transport: -30 to 70 °C / -22 to 158 °F
Particulate and Water Sealing Temperature INTERFACES Interfaces	60068-2-32 specification. Device with rubber boot: exceeds 600 hits at 0.5 m (300 cycle) per IEC 60068-2-32 specification. IP54 Operating: -20 to 50 °C / -4 to 122 °F Storage/Transport: -30 to 70 °C / -22 to 158 °F
Particulate and Water Sealing Temperature INTERFACES Interfaces SENSORS	60068-2-32 specification. Device with rubber boot: exceeds 600 hits at 0.5 m (300 cycle) per IEC 60068-2-32 specification. IP54 Operating: -20 to 50 °C / -4 to 122 °F Storage/Transport: -30 to 70 °C / -22 to 158 °F USB-C: High Speed USB 2.0 OTG

PHYSICAL CHARACTERISTICS	
Dimensions	16.0 x 7.1 x 1.7 cm / 6.2 x 2.7 x 0.66 in
Display	4 inch WVGA resolution 800 x 480; LED backlight; Touch Screen: 5 points multi-touch capacitive panel with Dragontrail hardened glass
Keys	Backlighted 24 keys rubber keyboard, plus two side scan keys and two programmable side keys
Weight	With Battery: 268 g / 9.4 oz
READING PERFORM	IANCE
Camera	Resolution: 8 MP; Illumination: LED flash; Lens: Auto focus
Scan Engine	2D Ultra slim area imager (supports 1D / 2D codes); Datalogic's 'Green Spot' for good-read feedback; Resolution: VGA (640 x 480 pixels)
Minimum Element Width	1D Linear: 0.101 mm / 4 mils; PDF417: 0.167 mm / 6.6 mils; Data Matrix: 0.190 mm / 7.5 mils
SAFETY & REGULA	TORY
Agency Approvals	The product meets necessary safety and regulatory approvals for its intended use.
Environmental Compliance	Complies to EU RoHS
SOFTWARE	
Applications	Datalogic SoftSpot technology for configurable soft triggers
Provisioning	QR Code enrollment
Configuration and Maintenance	Scan2Deploy Studio, DXU
Development	Java, Cordova and Xamarin SDK available
МДМ	Java, Cordova and Xamarin SDK available SOTI MobiControl, VMWare AirWatch, Ivanti Avalanche, 42Gears SureMDM
•	SOTI MobiControl, VMWare AirWatch, Ivanti Avalanche,
МДМ	SOTI MobiControl, VMWare AirWatch, Ivanti Avalanche,
MDM SYSTEM	SOTI MobiControl, VMWare AirWatch, Ivanti Avalanche, 42Gears SureMDM Micro-SD card slot: Compatible with Micro SD-HC cards,
SYSTEM Expansion Slots	SOTI MobiControl, VMWare AirWatch, Ivanti Avalanche, 42Gears SureMDM Micro-SD card slot: Compatible with Micro SD-HC cards, up to 64 GB; User-accessible
MDM SYSTEM Expansion Slots Memory	SOTI MobiControl, VMWare AirWatch, Ivanti Avalanche, 42Gears SureMDM Micro-SD card slot: Compatible with Micro SD-HC cards, up to 64 GB; User-accessible System RAM: 3 GB; eMMC Flash: 32 GB
MDM SYSTEM Expansion Slots Memory Microprocessor	SOTI MobiControl, VMWare AirWatch, Ivanti Avalanche, 42Gears SureMDM Micro-SD card slot: Compatible with Micro SD-HC cards, up to 64 GB; User-accessible System RAM: 3 GB; eMMC Flash: 32 GB 2 GHz Octa-core
MDM SYSTEM Expansion Slots Memory Microprocessor Operating System	SOTI MobiControl, VMWare AirWatch, Ivanti Avalanche, 42Gears SureMDM Micro-SD card slot: Compatible with Micro SD-HC cards, up to 64 GB; User-accessible System RAM: 3 GB; eMMC Flash: 32 GB 2 GHz Octa-core Android 9

ACCESSORIES

Base Stations/Chargers

SAVEO-M71CR Single Slot Dock



Miscellaneous

SAVEO-M71CR Belt Holster SAVEO-M71CR Rubber Boot





