

# SAVEO OMNI II

Introducing the next generation of omni directional, fixed standing barcode scanner. Featuring an ultra-high speed 2D CMOS scanning system, adjustable mounting bracket and auto-sensing, the SAVEO-OM-N12D is ideally suited to Commercial POS systems, Supermarkets, Transportation, Libraries, Postal Services, Banks, Telecoms, Industrial Manufacturing and many other automatic scanning applications.

## FEATURES

- HIGH PERFORMANCE OMNIDIRECTIONAL SCANNING
- ULTRA HIGH-SPEED AUTOSENSING (2600 FPS)
- DUAL LED OPTIMIZED ILLUMINATION ARRAY
- LED STATUS INDICATOR, AUDIBLE BEEPER
- SINGLE USB CABLE FOR POWER AND DATA
- PLUG AND PLAY DRIVERLESS OPERATION MODE
- MULTI-INTERFACE OPTIONS (USB HID, VCOM, RS232)
- COMPACT MODERN DESIGN (145 X 85 X 105 mm)



DESCRIPTION	P/N
2D Omnidirectional Barcode Scanner (2D CMOS, 2600FPS), Multi-Interface, OTG-HID (Default), USB Virtual COM Port, RS-232 serial modes) Adjustable Stand, USB Cable (for power and data)	SAVEO-OM-N12D

## Specifications

Performance characteristics	
Scan Engine	CMOS
Aiming LED	655nm Laser
Illumination Element	2x 625 nm LEDs
Depth of field	0-270mm
Scan Speed	2600 frames per sec (FPS)
Sensor	CMOS (1280 pixels H x 800 pixels V)
Best resolution	≥ 4mil
Reading angle	Yaw (Skew) 72° Pitch 82°
Print contrast	≥ 30°
Indicators	LED status Indicator & Audible Beeper
Interface	USB HID, USB Virtual COM Port, RS-232 (serial)
Triggering	Auto-sensing & Manual Scan Button

Electrical characteristics	
Input voltage	5 VDC ± 0.5 V
Current - operating	Operating 780mA, Idle 255mA

Physical characteristics	
Dimensions	145 X 85 X 105 mm (L x W x H)
Weight	465 g +/- 5 g (Without cable)

User Environment	
Operating temperature	-20°C to 50°C
Storage temperature	-20°C to 45°C
Humidity	5% to 85% relative humidity, non-condensing
Ambient Light	Maximum 96900Lux. (direct sunlight)

Symbologies	
PDF417, QRcode, Date Matrix, Maxicode, Aztec Code, MicroQR, Code39, FullASC II, Codebar, Industrial2of5, Interleave2of5, Matrix2of5, Code93, Code128, Code32, EAN 128, MSI, EAN 8&13, UPCA&E, Plessey, Hanxin Code.	

Packing details	
Inner Box	1pc/box; 140mm*120mm*170mm; 720g
Carton	20sets/ctn; 11.8kg/ctn; 690mm*420mm*255mm
Certifications	FCC, CE, RoHs