

# Saveo Print C1

Saveo Print C1 is a high-efficiency direct thermal label and barcode printer. Easy driver support for both Windows and Mac OS along with pre-set (and editable) paper media sizes & automatic media calibration allows for quick setup and configuration.

As Saveo Print C1 does not require any ink or toner, printed text and graphics are produced instantly, without mess and maintenance requirements often associated with other printing technologies.

Its automatic cutter can be set to cut each label individually or to cut at the end of each print run, easily within its simple UI print driver configuration panel.

Whether you are printing shipping or barcode labels for your business or badges for a school sports day, Saveo Print C1 brings efficiency, simplicity, and reliability in thermal printing in a small and reliable package.

## FEATURES

- SMALL FORM FACTOR (200 X 120 X 105mm)
- EXTENDED WIDE PAPER WIDTH (18-108mm)
- ELECTRONIC AUTO-CUTTER
- AUTO MEDIA CALIBRATION (TIMING)
- SIMPLE DRIVER UI CONFIGURATION TOOL
- WINDOWS & MAC OS DRIVER SUPPORT
- EXTENSIVE PRINTER LANGUAGE EMULATIONS INCL. TSPL(2), ZEBRA EPL, ZEBRA ZPL2, CPCL.



DESCRIPTION	P/N
High-efficiency Direct Thermal Label and Barcode printer with auto-cutter USB Cable, Power Adapter, Power cable.	SAVEO-PRINT-C1

## SPECIFICATIONS

Performance Characteristics	
Print Method	Direct Thermal
Resolution	203dpi
Max Printing Speed	150mm/s
Paper Width	48-108mm
Paper Thickness	0.08-0.18mm
Power Adapter	24V/2A (PSU included)
Print Head Life	TPH 30Km
Connection	USB (Cable included)
Operating Environment Humidity	10-90%
Operating Temperature	-10 to 50°C
Storage Temperature	-40 to 80°C
Weight	1.15kg
Dimensions	L200mm*W120mm*H105mm
Certifications	CE, FCC

